

CLAIMS:

1. A multiple-slide die-casting machine including a base, at least a guideway having side walls and two opposed ends mounted on the base, at least two clamping assemblies guided within the respective ends of the guideway for advancing and retracting slide mold sections towards and away from each other, and an injection system for introducing pressurised casting material into a cavity between the slide mold sections when the slide mold sections are in a molding position in which the slide mold sections are restrained together in a preloaded state, the multiple-slide die-casting machine comprising:

at least two brackets supported on said base for operatively securing the respective clamping assemblies; and

a reinforcement means for interconnecting said brackets to inhibit deflection of said base and said brackets induced by the force generated by said clamping assemblies for maintaining the preloaded state;

wherein each of said clamping assemblies comprises a clamping mechanism and a shank, said shanks being slidable in one of the ends of the guideway and being connected at a first end to one of the slide mold sections and coupled at a second end to said clamping mechanism, and wherein at least one slide mold section is connected to a respective one of the shanks by a mating engagement and a clamp for quick coupling of the slide mold section with the shank.

2. A multiple-slide die-casting machine as claimed in claim 1 wherein each said slide mold section comprises a mold portion and a mounting plate for connecting said mold portion to a respective one of said shanks.

10092557, 030802

3. A multiple-slide die-casting machine as claimed in claim 2, wherein said mating engagement is a co-operating keyway and slot.

4. A multiple-slide die-casting machine as claimed in claim 2, wherein said mounting plate are adapted for connecting mold portions of varying dimension configurations to a shank of a given dimension configuration.

5. A multiple-slide die-casting machine as claimed in claim 1, wherein at least one of the slide mold sections has an ejection mechanism for ejecting a molded product out of the slide mold section.

6. A multiple-slide die-casting machine as claimed in claim 5, wherein the ejection mechanism has at least one ejector pin slidably engaged in the slide mold section, the ejector pin emerging into the cavity of the slide mold section when the slide mold sections are retracted away from each other, and retracting into the slide mold when the slide mold sections are advanced toward each other.

7. A multiple-slide die-casting machine as claimed in claim 6, wherein the ejector pin is displaced by an ejector hub slidably received in a cavity of respective ones of the shanks.

8. A multiple-slide die-casting machine as claimed in claim 7, wherein displacement of the ejector hub is guided by at least one stop pin secured to one of the side walls and abutting against portions of the ejector hub to limit a stroke of displacement thereof.

100925567-030800

9. A multiple-slide die-casting machine as claimed in claim 1 wherein said base comprises a base plate for supporting the respective brackets at a first side, said reinforcement means is a reinforcement member being spaced apart from said base plate to connect said respective brackets at a second side so that the respective clamping assemblies are operatively secured between said base plate and said reinforcement member.

10. A multiple-slide die-casting machine as claimed in claim 9 wherein said reinforcement member is a flat ring parallel to said base plate.

11. A multiple-slide die-casting machine as claimed in claim 1 wherein said shank is coupled to said clamping mechanism through a ram and a coupling mechanism.

12. A multiple-slide die-casting machine as claimed in claim 11 wherein a respective pair of stops are provided between each of said brackets and each of said rams to ensure the precise molding position of the slide mold sections and to permit a substantial portion of the clamping force to be applied to said brackets to achieve pre-loading of said clamping assemblies.

13. A multiple-slide die-casting machine as claimed in claim 1, wherein respective ones of the shanks have a positive stop for aligning the slide mold section thereon during the mating engagement.

14. A multiple-slide die-casting machine as claimed in claim 1 wherein each of said clamping mechanisms is adjustably secured to a corresponding one of said brackets

10092567.030800

to ensure the necessary pressure of the clamping assemblies for maintaining the preloaded state as predetermined.

15. A multiple-slide die-casting machine as claimed in claim 1 wherein said injection system comprises an injection plunger advanceable and retractable by an hydraulic cylinder, and a control system having a closed loop control mode for selective use to control an operation of a hydraulic cylinder during an injection cycle from a velocity phase in which a velocity of the injection plunger follows a predetermined profile, to a pressure phase in which a net hydraulic pressure applied to the injection plunger is controlled.

16. A multiple-slide die-casting machine as claimed in claim 15 wherein the control system further has an open loop control mode for selective use to control the operation of the hydraulic cylinder with a pre-set pressure and a flow rate of hydraulic fluid supplied to the hydraulic cylinder.

17. A multiple-slide die-casting machine as claimed in claim 16 wherein the control system comprises a control mode selection valve which is automatically activated to enable the pre-set pressure set on a pressure reducing valve only when the open loop control mode is selected.

18. A multiple-slide die-casting machine as claimed in claim 16 wherein the control system comprises at least a position transducer for detecting a pre-set position of the injection plunger and generating a signal to start a transition from the velocity phase to the pressure phase.

100925567 030802

19. A multiple-slide die-casting machine comprising:

a base plate;

a guide member, defining two guideways crossing and disposed perpendicular to each other, each guideway having side walls and two opposed ends;

a respective clamping assembly guided within each of the ends of each guideway for advancing and retracting a slide mold section towards and away from a centre of the guideway;

an injection system for introducing pressurised casting material into a cavity between the slide mold sections when the slide mold sections are in a molding position in which the slide mold sections are restrained together in a preloaded state;

a respective bracket including a first surface secured to said base plate and a second surface remote from said base plate, operatively securing each of said clamping assemblies between said first and second surfaces thereof; and

interconnecting means for interconnecting said second surfaces of said brackets so that the respective clamping assemblies are operatively secured between said base plate and said interconnecting means and deflection of said base plate and said brackets induced by force generated by said clamping assemblies for maintaining the preloaded state is inhibited;

wherein each of said clamping assemblies comprises a clamping mechanism and a shank having opposed ends, the shank being slidable between the side walls in one of the ends of one guideway, and connected at a first end thereof to one of the slide mold sections and coupled at a second end thereof to the clamping mechanism, and wherein at least

1009557.030800
"00000" 49525001

one slide mold section is connected to a respective one of the shanks by a mating engagement and a clamp for quick coupling of the slide mold section with the shank.

20. A multiple-slide die-casting machine as claimed in claim 19 wherein each said slide mold section comprises a mold portion and a mounting plate for connecting said mold portion to a respective one of said shanks.

21. A multiple-slide die-casting machine as claimed in claim 20, wherein said mating engagement is a co-operating keyway and slot.

22. A multiple-slide die-casting machine as claimed in claim 20, wherein said mounting plate are adapted for connecting mold portions of varying dimension configurations to a shank of a given dimension configuration.

23. A multiple-slide die-casting machine as claimed in claim 19 wherein said interconnecting means is a flat interconnecting ring.

24. A multiple-slide die-casting machine as claimed in claim 23, wherein respective ones of the shanks have a positive stop for aligning the slide mold section thereon during the mating engagement.

25. A multiple-slide die-casting machine as claimed in claim 23, wherein at least one of the slide mold sections has an ejection mechanism for ejecting a molded product out of the slide mold section.

10092557, 030802

26. A multiple-slide die-casting machine as claimed in claim 25, wherein the ejection mechanism has at least one ejector pin slidably engaged in the slide mold section, the ejector pin emerging into the cavity of the slide mold section when the slide mold sections are retracted away from each other, and retracting into the slide mold when the slide mold sections are advanced toward each other.

27. A multiple-slide die-casting machine as claimed in claim 26, wherein the ejector pin is displaced by an ejector hub slidably received in a cavity of respective ones of the shanks.

28. A multiple-slide die-casting machine as claimed in claim 27, wherein displacement of the ejector hub is guided by at least one stop pin secured to one of the side walls and abutting against portions of the ejector hub to limit a stroke of displacement thereof.

29. A multiple-slide die-casting machine as claimed in claim 19 wherein said shank is coupled to said clamping mechanism through a ram and a coupling.

30. A multiple-slide die-casting machine as claimed in claim 29 wherein said coupling comprises a pivotal coupling member adapted to transfer a translation of said clamping mechanism to a translation of said shank and to compensate for any misalignment between said clamping mechanism and said shank.

31. A multiple-slide die-casting machine as claimed in claim 29 wherein a respective pair of stops are provided between each of the brackets and each of the rams to ensure

10092567 030800

the precise molding position of the slide mold sections and to permit a substantial portion of the clamping force to be applied to said brackets to achieve pre-loading of said clamping assemblies.

32. A multiple-slide die-casting machine as claimed in claim 19 wherein each of said clamping mechanisms is adjustably secured to a corresponding one of said brackets to ensure the desired force generated by the clamping assemblies for maintaining the preloaded state as predetermined.

208020 49526001